

Motorized Stainless Steel Ball Valve

2-Way Configuration | NPT Thread | 1-1/2" to 2"

A compact, threaded Stainless Steel Ball Valve with integrated electric actuator, designed for automated flow control up to 185 psi.



Features

- Electric motorized actuation
- Full port design
- High flow capacity
- Durable with long lifespan
- Anti-water hammer performance
- Power required during actuation only
- Suitable for continuous duty applications
- IP67 (NEMA 4 equivalent) rated actuator enclosure
- Easy to install

Industrial Applications

- Process Water Control
- Compressed Air Systems
- Food and Beverage Processing Equipment
- General Chemical Handling (Non-Aggressive Media)
- HVAC and Building Automation
- Water Distribution Lines
- Filtration Systems

*These are not intended for use in medical life support, combustion, aviation, aerospace, automotive or similar applications.

Approvals

- CE compliant (EMC Directive 2014/30/EU)
- EMC compliant (EN 61000 series)

Valve Specification

Pipe Connection		Operating Pressure (psi)		Media Temperature (°F)		Compatible Actuators
Size (in)	Thread Connection	Min	Max	Min	Max	
1-1/2	NPT - Female	0	185	35	200	XR22-A100
2	NPT - Female	0	185	35	200	XR22-A100

Materials of Construction


Valve Parts	Material
Body	304 Stainless Steel
Components	Stainless Steel
Ball Seat	PTFE
Seal	EPDM

*Consult a chemical compatibility expert for correct seal and valve body material choice.

Actuator Electrical Data

Actuator	Wiring Type	Actuation Method	Working Current	Supply Voltage	Actuator Connection
XR22-A100	2-Wire	Capacitor-Assisted	≤ 1 A	9-24V AC/DC, 110-230V AC	Lead Wires

Actuator Wiring Diagram




Actuator Operational Information

Actuator	Fail Position	Ambient Temperature (°F)	Max Torque (Nm)	Duty Rating ⁽¹⁾	Min. Energized Time (s)	Recommended Maximum Cycling Rate	Open / Close Time
XR22-A100	Fail Close	5 to 120	10	100% ED	60	≤ 45 cycles/hour	≤ 15 sec

(1) Duty rating is at ambient temperature

Motorized Stainless Steel Ball Valve

2-Way Configuration | NPT Thread | 1-1/2" to 2"




Parts List

No.	Valve Parts	Material	Qty
1	Actuator	PPO	1
2	Valve Body	SS304	1
3	O-Ring	EPDM	2
4	Sealing Gasket	PTFE	1
5	Seat	PTFE	1
4	Ball	SS304	1
7	Gasket	PTFE	1
8	Stem	SS304	1
9	O-Ring	EPDM	2

Dimension - Metric

Pipe Size (in)	Dimension (mm)						
	D1/D2	d ±0.3	L1 ±1.0	L2 ±1.0	E1 ±0.5	H1 ±1.0	H2
1-1/2	1/2"	38	111.4	26	54	128.5	36
2	3/4"	49	130	27	66	136.5	45

Product Ordering Code



EXAMPLE:

BVS9CE-XR22-J - Indicates a Stainless Steel Ball Valve, 2 way, 2" port size, EPDM seal, XR22-A100 actuator 2 wire auto return, 9 to 24 VAC/DC